INDIVIDUAL LOUDSPEAKERS



4C3Z8OT

MOISTURE RESISTANT

4" O.D. Moisture Resistant Loudspeaker, 5 oz. magnet, 8Ω impedance

GENERAL DESCRIPTION

The 4C3Z8OT is 4" square frame loudspeaker with a 5 oz. magnet and an 8 Ohm nominal impedance.

INTENDED USE - Indoor and Outdoor Environment

Program Material Installation

Signal tones, voice and music

Loudspeaker mount is a #8-32 tapped hole,

center rear of device

AUDIO SPECIFICATIONS

Frequency Response Power Handling¹ Impedances Available

130 Hz - 9kHz 10W

Cone Finish Options

8-Only


Weather-Resistant

Magnet Material Weight


Ceramic 4.8 oz

Depth 1.465 in





Recommended construction sequences, installation instructions, and A&E Specifications are available in various formats in the QUAM Architects' and Engineers' Resources section on the web at: www.QuamSpeakers.com









QUAM-NICHOLS COMPANY, INC. 234 East Marquette Rd. Chicago, IL. 60637 Tel: 1-800-NEED-NOW (800-633-3669) Fax: 1-888-NEED-NOW (888-633-3669) e-mail: NeedNow@QNC.com www.QuamSpeakers.com

¹Loudspeaker Power Rating per EIA 426A